

KOLD KING CAB CHASSIS

AVAILABLE SIZES

Width	Length	Height					
		79"	85"	91"	97"	103"	109"
96"	12'	●	●	●			
	14'	●	●	●			
	16'	●	●	●	●		
	18'		●	●	●		
	20'		●	●	●	●	
	22'		●	●	●	●	●
	24'		●	●	●	●	●
	26'			●	●	●	●
28'				●	●	●	
102"	18'		●	●	●		
	20'		●	●	●	●	
	22'		●	●	●	●	●
	24'		●	●	●	●	●
	26'			●	●	●	●
	28'				●	●	●

• Available sizes limited by chassis type

FEATURES

Side Walls	<ul style="list-style-type: none"> • .040" Smooth aluminum pre-painted white panels • Galvanized-steel Z-wall posts with spruce/pine/fir build ups
Front	<ul style="list-style-type: none"> • Insulated FiberPanel® PW (FRP) front wall • Molded-composite front corner wind deflector with fiberglass dormer • Extruded-aluminum radius vertical front corners
Lining	<ul style="list-style-type: none"> • .090" Seamless glass board lining on side walls and ceiling
Insulation	<ul style="list-style-type: none"> • 3" Polyurethane foam – side walls, ceiling, above cross members in floor • 4" Polyurethane foam – front wall
Rear Frame	<ul style="list-style-type: none"> • Painted galvanized steel • 14 ga. Header • 12 ga. Corner posts • 10 ga. One-piece V-groove threshold • Aluminum drip rail over rear door • Internal gussets
Rear Door	<ul style="list-style-type: none"> • Medium-temp insulated roll-up • Safety release and lockable hasp
Floor	<ul style="list-style-type: none"> • Smooth box-type extruded-aluminum (no subfloor) • Four Kazoo drains
Subframe	<ul style="list-style-type: none"> • 3" I-beam cross members on 12" C/L • 4" I-beam longills • Full-perimeter steel reinforcing aluminum rub rail • .060" Seamless fiberglass splash pan above cross members • Pre-coated understructure
Roof	<ul style="list-style-type: none"> • One-piece .032" aluminum skin • Galvanized-steel roof bows on 24" C/L
Interior Lights	<ul style="list-style-type: none"> • LED dome light with rear switch - hot wired
Exterior Lights	<ul style="list-style-type: none"> • LED clearance lights • Existing chassis taillights
Bumper	<ul style="list-style-type: none"> • Pooched ICC
Additional Features	<ul style="list-style-type: none"> • Two rear grab handles
Warranty	<ul style="list-style-type: none"> • 1-year white surface and leaks • 3-year/36,000-mile limited bulkhead-to-bumper warranty • 5-year limited structural warranty (roof, wall and floor structure) • See our warranty policy for details

AVAILABLE OPTIONS

Side Walls	<ul style="list-style-type: none"> • Aluminum contoured rubrail (hat section)
Front	<ul style="list-style-type: none"> • Insulated bulkhead (2", 3", 4") - movable and stationary • Polished-aluminum cast front corners
Lining	<ul style="list-style-type: none"> • 1/4" FiberPanel® PW (FRP) • ArmorTuf®-NXT
Scuff	<ul style="list-style-type: none"> • Smooth or corrugated in galvanized steel • Smooth or corrugated in aluminum
Insulation	<ul style="list-style-type: none"> • 4" Polyurethane foam (walls, ceiling, floor) • 5" Polyurethane foam (walls, ceiling, floor) • 6" Polyurethane foam (ceiling, floor - between cross members only)
Side Door	<ul style="list-style-type: none"> • Single-swing • Double-swing
Rear Frame	<ul style="list-style-type: none"> • Stainless-steel
Rear Door	<ul style="list-style-type: none"> • Low-temp insulated roll-up • Full-opening swing • Three-panel full-opening swing
Steps	<ul style="list-style-type: none"> • Stirrup • Pull-out RV • Bustin slide-away • Insulated aluminum recessed stepwell
Floor	<ul style="list-style-type: none"> • Anti-skid box-type reefer • Anti-skid inverted "T" • Additional Kazoo floor drains • Wheel wells • Forklift reinforcement (18' and longer)
Ramp	<ul style="list-style-type: none"> • Aluminum slider (10', 12', 14', 16')
Interior Lights	<ul style="list-style-type: none"> • Additional LED dome light
Cargo Control	<ul style="list-style-type: none"> • E-Track • F-Track • Rope ties • Floor ties
Bumpers	<ul style="list-style-type: none"> • Full-width pooched ICC • Full-width two-step pooched ICC • One-way pooched step • Full-width pooched step • Chicago-style step • Rubber dock
Accessories	<ul style="list-style-type: none"> • Hitch receiver • Rear spot-view mirror - stainless steel • Back-up camera • Back-up alarm • Tire chocks • Reflector Kit • Fire extinguisher • First aid kit
Liftgate	<ul style="list-style-type: none"> • Contact a Supreme Sales Representative for available options

Due to Supreme Corporation's commitment to product improvement and quality, specifications and options are subject to change without notice.